

SKIRSTOMOJO KALNELIO IR KAUPIAMOJO KELYNO IŠILGINIO PROFILIO PARAMETRAI

5.1 lentelė. Mažo galingumo skirstomojo kalnelio išilginio profilio parametrai „sudėtingam“ keliui Nr. 1

Ruožo ilgis $l_j, \text{ m}$	Nuolydis $i_j, \text{ ‰}$	Profilio aukštis $h_j = l_j * i_j * 10^{-3}, \text{ m}$	Bendras profilio aukštis, m
$l_{c1} = 6,25$	$i_{c1} = 8,4$	$h_{c1} = 0,05$	0,05
$l_{c2} = 6,25$	$i_{c1} = 41,6$	$h_{c2} = 0,26$	0,31
$l_{ck1} = 21,36$	$i_{ck1}^{\max} = 47$ $i'_{ck1} = 44$	$h_{ck1}^{\max} = 1,00$ $h'_{ck1} = 0,94$	1,25
$l_{ck2} = 55,31$	$i_{ck2} = 18,08$ $i'_{ck2} = 19,1$	$h'_{ck2} = 1,06$	2,31
$l_{s1} = 25$	$i_{s1}^{\min} = 12$	$h_{s1}^{\min} = 0,30$	2,61
$l_{tarp} = 63,58$	$i_{tarp}^{\min} = 7$	$h_{tarp}^{\min} = 0,45$	3,06
$l_{s2} = 28,97$	$i_{s2}^{\min} = 7$	$h_{s2}^{\min} = 0,20$	3,26
$l_c = 89,1$	$i_c = 2$	$h_c = 0,18$	3,44
$l_{kk1} = 53,63$	$i_{kk1} = 2$	$h_{kk1} = 0,11$	3,55
$l_{s3} = 15,48$	$i_{s3} = 1,5$	$h_{s3} = 0,02$	3,57
$l_{kk2} = 50$	$i_{kk2} = 0,6$	$h_{kk2} = 0,03$	3,6

5.2 lentelė. Didelio galingumo skirstomojo kalnelio išilginio profilio parametrai „sudėtingam“ keliui Nr. 1

Ruožo ilgis l_j , m	Nuolydis i_j , ‰	Profilio aukštis $h_j = l_j * i_j * 10^{-3}$, m	Bendras profilio aukštis, m
$l_{c1} = 6,25$	$i_{c1} = 8,4$	$h_{c1} = 0,05$	0,05
$l_{c2} = 6,25$	$i_{c1} = 41,6$	$h_{c2} = 0,26$	0,31
$l_{ck1} = 21,36$	$i_{ck1}^{\max} = 47$ $i_{ck1}' = 44,25$	$h_{ck1}^{\max} = 1,00$ $h_{ck1}' = 0,95$	1,26
$l_{ck2} = 55,31$	$i_{ck2} = 18,26$ $i_{ck2}' = 19,2$	$h_{ck2}' = 1,06$	2,32
$l_{s1} = 25$	$i_{s1}^{\min} = 12$	$h_{s1}^{\min} = 0,30$	2,62
$l_{tarp} = 63,58$	$i_{tarp} = 12$	$h_{tarp} = 0,79$	3,41
$l_{s2} = 28,97$	$i_{s2}^{\min} = 7$	$h_{s2}^{\min} = 0,20$	3,61
$l_c = 89,1$	$i_c = 2$	$h_c = 0,18$	3,79
$l_{kk1} = 53,63$	$i_{kk1} = 2$	$h_{kk1} = 0,11$	3,90
$l_{s3} = 15,48$	$i_{s3} = 1,5$	$h_{s3} = 0,02$	3,92
$l_{kk2} = 50$	$i_{kk2} = 0,6$	$h_{kk2} = 0,03$	3,95