

SKIRSTOMOJO KALNELIO IR KAUPIAMOJO KELYNO IŠILGINIO PROFILIO PARAMETRAI

6.5 lentelė. Didelio galingumo skirstomojo kalnelio išilginio profilio parametrai „sudėtingam“ keliui Nr. 1

Ruožo ilgis l_j, m	Nuolydis i_j, ‰	Profilio aukštis $h_j = l_j * i_j * 10^{-3}$, m	Bendras profilio aukštis, m
$l_{c1} = 5,00$	$i_{c1} = 6,68$	$h_{c1} = 0,03$	0,03
$l_{c2} = 5,00$	$i_{c1} = 33,32$	$h_{c2} = 0,17$	0,20
$l_{ck1} = 18,15$	$i_{ck1}^{\max} = 47$ $i_{ck1}' = 44$	$h_{ck1}^{\max} = 0,85$ $h_{ck1}' = 0,94$	1,05
$l_{ck2} = 48,35$	$i_{ck2} = 26,27$ $i_{ck2}' = 19,1$	$h_{ck2}' = 1,27$	2,32
$l_{s1} = 25$	$i_{s1}^{\min} = 12$	$h_{s1}^{\min} = 0,30$	2,62
$l_{tarp} = 63,58$	$i_{tarp}^{\min} = 7$	$h_{tarp}^{\min} = 0,45$	3,07
$l_{s2} = 25,0$	$i_{s2}^{\min} = 7$	$h_{s2}^{\min} = 0,18$	3,25
$l_c = 75,6$	$i_c = 2$	$h_c = 0,15$	3,40
$l_{kk1} = 53,63$	$i_{kk1} = 2$	$h_{kk1} = 0,11$	3,51
$l_{s3} = 6,25$	$i_{s3} = 1,5$	$h_{s3} = 0,01$	3,52
$l_{kk2} = 50$	$i_{kk2} = 0,6$	$h_{kk2} = 0,03$	3,55

6.6 lentelė. Didelio galingumo skirstomojo kalnelio išilginio profilio parametrai „sudėtingam“ keliui Nr. 1

Ruožo ilgis l_j, m	Nuolydis i_j, ‰	Profilio aukštis $h_j = l_j * i_j * 10^{-3}$, m	Bendras profilio aukštis, m
$l_{c1} = 6,25$	$i_{c1} = 8,4$	$h_{c1} = 0,05$	0,05
$l_{c2} = 6,25$	$i_{c1} = 41,6$	$h_{c2} = 0,26$	0,31
$l_{ck1} = 22,95$	$i_{ck1}^{\max} = 47$ $i_{ck1}' = 43,48$	$h_{ck1}^{\max} = 1,08$ $h_{ck1}' = 1,00$	1,31
$l_{ck2} = 55,31$	$i_{ck2} = 17,0$ $i_{ck2}' = 18,44$	$h_{ck2}' = 1,02$	2,33
$l_{s1} = 28,95$	$i_{s1}^{\max} = 18,44$	$h_{s1}^{\max} = 0,53$	2,86
$l_{tarp} = 65,88$	$i_{tarp} = 11,69$	$h_{tarp} = 0,77$	3,63
$l_{s2} = 28,95$	$i_{s2}^{\min} = 7$	$h_{s2}^{\min} = 0,20$	3,83
$l_c = 92,97$	$i_c = 2$	$h_c = 0,19$	4,02
$l_{kk1} = 53,63$	$i_{kk1} = 2$	$h_{kk1} = 0,11$	4,13
$l_{s3} = 15,48$	$i_{s3} = 1,5$	$h_{s3} = 0,02$	4,15
$l_{kk2} = 50$	$i_{kk2} = 0,6$	$h_{kk2} = 0,03$	4,18